

IP CCTV / Professional IP cameras / Uniview - Uniarch / Turret cameras

UV-IPC3613LB-AF28K-G

Uniview



Features

- Uniview
- Turret IP Camera
- EasyBasic range
- 1/2.7" Progressive Scan CMOS
- 3 Megapixel (1920x1080)
- 2.8 mm Lens
- IR range of 30 m
- WDR 120dB
- Compression Ultra265/H.265/H.264
- Integrated microphone
- PoE IEEE802.3af
- Weatherproof IP67
- Surge protection
- Slot for microSD up to 128GB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Uniview
Range	Prime
Image sensor	1/2.7" Progressive Scan CMOS
Maximum resolution	3 Megapixel (1920x1080)
Main Stream rate	1080P (1920*1080)@30fps; 720P (1280*720)@30fps;
Extra Stream rate	720P (1280*720)@30fps; D1 (720*576)@30fps; 640*360@30fps; 2CIF(704*288)@30fps; CIF(352*288)@30fps
Compression	Ultra265/H.265/H.264
Lens	2.8 mm
Range performance	Detection 42 m Remark 16,8 m Recognition 8,4 m Identification 4,4 m
FOV	H= 112.9° V= 59.1° O= 121.2°
Minimum illumination	0.002 Lux (Colour)
Infrared range	30 m
Image improvements	WDR 120dB, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask, Smart IR
Day / Night	Automatic and configurable
Internal memory	Slot for microSD card up to 128GB
Alarms	Does not have
Audio	Integrated microphone
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF
Power	DC 12 V / 7 W, PoE IEEE802.3af
Temp. operation	-30° C ~ 60° C
Degree of protection	Waterproof IP67, Surge protection

Dimensions

2118 x 95mm

Weight

300 g
