

UV-UHO-S2E-M3

Uniarch



Features

- Uniarch
- PT IP Dome Camera
- 1/3" Progressive Scan CMOS
- 3 Megapixel (2304x1296)
- 4 mm Lens
- 0,02 Lux
- IR Range 10m
- Compression H.265/H.264
- WIFI
- RJ-45 10/100 BaseT
- Includes Microphone and Speaker
- MicroSD card slot up to 256 GB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- Power supply 5 VDC included

Specifications

Range	Uniarch
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	3 Megapixel (2304x1296)
Main Stream rate	3 Mpx@25fps; 2 MPx@30fps; 720P (1280x720)@30fp
Extra Stream rate	640x360@25fps; 2CIF (704x288)@25fps; CIF (352x288)@25fps
Compression	H.265/H.264
WIFI	2.4G Wi-Fi (IEEE802.11b/g/n)
Lens	4 mm
Minimum illumination	0.02 Lux (Colour)
Infrared range	10 m
PTZ range	Pan 0° ~ 340°/ tilt-5° ~ 55°
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card slot up to 256 GB
Autotracking	Yes
Human detection	Yes
Alarms	Does not have
Audio	Includes microphone and speaker
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF
Power	DC 5 V / 1.5 A
Temp. operation	-10° C ~ 55° C
Degree of protection	Weatherproof IP67
Dimensions	Ø80 x 121 (h) mm

Weight

180 g
